

Air Suspension Bearing Co., Ltd

NTN HK1312D needle roller bearings



HK1312D Bearing 2D drawings and 3D CAD models

Bearing No. HK1312D

| Size | 13x19x12 mm |
|---|--------------|
| Bore Diameter | 13,000 mm |
| Outer Diameter | 19,000 mm |
| Width | 12,000 mm |
| Fw | 13,000 mm |
| D | 19,000 mm |
| С | 12,000 mm |
| Dw | 2 mm |
| Lw | 7.3 mm |
| Lubrication hole on outer ring | Oui/Yes |
| k | 2 mm |
| Inner ring reference | IR10X13X12.5 |
| Mass | 0.01 kg |
| Cr | 6.95 kN |
| C0r | 7.9 kN |
| Nlim (grease) | 12,000 rpm |
| Nlim (oil) | 18,000 rpm |
| Min operating temperature, Tmin | -20 ° C |
| Max operating temperature, Tmax | 120 ° C |
| Characteristic cage frequency, FTF | 0.43 Hz |
| Characteristic rolling element frequency, BSF | 7.37 Hz |
| Characteristic outer ring frequency, BPF0 | 6.5 Hz |
| | |



Air Suspension Bearing Co., Ltd

| Characteristic inner ring | 8.5 Hz |
|---------------------------|--------|
| frequency, BPFI | |